



NOTES:

1. UNITS: [mm] in
2. ALIGNMENT EDGE SHOULD BE NO HIGHER THAN .19 [4.8] TO AVOID INTERFERENCE WITH COVER.
3. [-A-] & [-B-] ARE DEFINED AS REFERENCE SURFACES.
4. CONNECTOR: MS27476Y10D35P
MATES WITH: MS27473T10B35S
5. SENSITIVE AXIS LABEL VARIES BY MODEL.

CONN. PIN	FUNCTION
1	FACTORY USE
2	FACTORY USE
3	CASE GROUND
4	+SERIAL PORT
5	-SERIAL PORT
6	FACTORY USE
7	FACTORY USE
8	FACTORY USE
9	FACTORY USE
10	FACTORY USE
11	PWR RTN
12	+PWR
13	FACTORY USE

DIMENSIONS ARE IN INCHES AND APPLY TO PART BEFORE FINISHING	
TOLERANCE UNLESS SPECIFIED	
TWO PLACE DECIMALS	(.00) ± .01
THREE PLACE DECIMALS	(.000) ± .005
ANGLES	± 1°
RAW MATL - COMMERCIAL STANDARD	

Jewell Instruments
MANCHESTER, NH
TRIPLETT MODUTEC A&M EMICO

PROPRIETARY NOTICE
THIS DOCUMENT IS THE PROPERTY OF JEWELL INSTRUMENTS, LLC. NEITHER THIS DOCUMENT NOR THE DATA CONTAINED HEREIN SHALL BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN AUTHORIZATION OF JEWELL INSTRUMENTS, LLC. NO RIGHT IS GRANTED TO DISCLOSE OR SO USE ANY INFORMATION CONTAINED HEREIN. ALL RIGHTS RESERVED.

TITLE DX-100 SERIES OUTLINE DRAWING	
DRAWING NO. OD02550282-000	REV C
SCALE 1:1	CAGE CODE 33005 SHEET 1 OF 1