



NOTES:

- UNITS: [mm]
in
- ALIGNMENT EDGE SHOULD BE NO HIGHER THAN .19 [4.8] TO AVOID INTERFERENCE WITH COVER.
- A- & -B- ARE DEFINED AS REFERENCE SURFACES.
- CONNECTOR: MS27476Y10D35P
MATES WITH: MS27473T10B35S
- SENSITIVE AXIS LABEL VARIES BY MODEL.

CONN. PIN	FUNCTION
1	FACTORY USE
2	FACTORY USE
3	CASE GROUND
4	+SERIAL PORT
5	-SERIAL PORT
6	FACTORY USE
7	FACTORY USE
8	FACTORY USE
9	FACTORY USE
10	FACTORY USE
11	PWR RTN
12	+PWR
13	FACTORY USE

DIMENSIONS ARE IN INCHES AND APPLY TO PART BEFORE FINISHING
TOLERANCE UNLESS SPECIFIED
TWO PLACE DECIMALS (.00) ± .01
THREE PLACE DECIMALS (.000) ± .005
ANGLES ± 1°
RAW MATL - COMMERCIAL STANDARD



MANCHESTER, NH
TRIPLETT MODUTEC A&M EMICO

PROPRIETARY NOTICE
THIS DRAWING IS THE PROPERTY OF JEWELL INSTRUMENTS, LLC. NEITHER THIS DOCUMENT NOR THE DATA CONTAINED HEREIN SHALL BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN AUTHORIZATION OF JEWELL INSTRUMENTS, LLC. NO RIGHT IS GRANTED TO DISCLOSE OR SO USE ANY INFORMATION CONTAINED HEREIN. ALL RIGHTS RESERVED.

TITLE
**DX-200 SERIES
OUTLINE DRAWING**

DRAWING NO. **OD02550283-000** REV **C**

SCALE **1:1** CAGE CODE **33005** SHEET **1 OF 1**